

PowerWalker VI 600 SE

Line-Interactive UPS System

600VA Line-Interactive UPS

2x Schuko outlets, RJ11/RJ45 Surge Protection


USB Connection for monitoring

Cold start, built-in boost and buck AVR function

Green power function for energy saving




Item-No. 10120007



Product Features

PowerWalker VI 600 SE provides comprehensive protection and high power density in small and economic package. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or small office application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- Green function for energy saving



Technical Details

Product Features

Capacity	600VA/360W
Input Voltage	220/230/240VAC
Input Voltage Range	170-280VAC \pm 7%
Output Voltage	220/230/240VAC
Voltage Regulation (Battery Mode)	\pm 10%
Output Frequency	50Hz or 60Hz
Frequency Regulation (Battery Mode)	\pm 1Hz
Output Waveform	Simulated Sine Wave

Battery

Type	12V / 7Ah
Quantity	1x
Recharge Time	6h for 90% after complete discharge

Transfer Time

Typical	2-6 ms
----------------	--------

LED Indicators

AC Mode	green LED lighting
Battery Mode	green LED flashing

Audio Indicators

Battery Mode	Beep every 10 sec
Low Battery	Beep every second
Batt. Replacement	Beep every 2 sec
Fault	Continuous Beep
Overload	Beep every 0,5 sec

Full Protection

Discharge prevention	Yes
Deep discharger	Yes
Overcharge	Yes
Overload	Yes

Connections

Interface	USB
Outlets	2x Schuko
Surge Protection	RJ11/RJ45 (in/out)

Software & System Requirements

Software	WinPower
Operating System	For details visit: www.powerwalker.com/winpower.html
Other	1x USB port

Product Details

Dimensions	333 x 111 x 143 mm
Colour	Black
Weight	5.4 kg
Model Code	VI 600 SE

Environment

Temperature	0°C – 40°C
Humidity	0% - 90% (non- condensing)

Package Content

Package Content	PowerWalker VI 600 SE, USB cable, Software CD, manual
------------------------	--

Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/CS
Manual Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/CS
Dimension/Giftbox	391 x 157 x 215 mm
Weight/Giftbox	5.9kg
Pieces/Carton	3pcs
Dimension/Carton	495 x 410 x 252 mm
Weight/Carton	18.2kg
Pieces/Palette	96pcs
Item Number	10120007
EAN	4260074971323
Warranty	24 Month (except battery)

Version: EN 30/04/2012

We reserve the right for technical changes and mistakes

Use UPS configurator on www.powerwalker.com for detailed backup time information.